

Temperature / Humidity Chambers

Floor Model Units



LR-HD-400 Series
LR-HD-500 Series
LR-HD-200 Series

Unit Specifications

Model	Working Volume	Dimensions (H x W x D)	Temperature Range	Temperature Rise Time	Temperature Pull Down	Humidity Range	Power Required
LR-HD-405	5 Cubic Ft.	Int: 20" x 22" x 20" Ext: 69" x 31" x 44"	-17°C to +177°C 0°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 20 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-408	8 Cubic Ft.	Int: 24" x 24" x 24" Ext: 70" x 33" x 48"	-17°C to +177°C 0°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 20 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-410	10 Cubic Ft.	Int: 28" x 24" x 27" Ext: 71" x 33" x 52"	-17°C to +177°C 0°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 20 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-413	13 Cubic Ft.	Int: 28" x 28" x 28" Ext: 71" x 37" x 52"	-17°C to +177°C 0°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 20 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 3 Phase 60 Hz
LR-HD-421	21 Cubic Ft.	Int: 32" x 32" x 32" Ext: 76" x 41" x 52"	-17°C to +177°C 0°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 20 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 3 Phase 60 Hz
LR-HD-505	5 Cubic Ft.	Int: 20" x 22" x 20" Ext: 69" x 31" x 44"	-37°C to +177°C -35°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 35 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-508	8 Cubic Ft.	Int: 24" x 24" x 24" Ext: 70" x 33" x 48"	-37°C to +177°C -35°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 35 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-510	10 Cubic Ft.	Int: 28" x 24" x 27" Ext: 71" x 33" x 52"	-37°C to +177°C -35°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 35 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-513	13 Cubic Ft.	Int: 28" x 28" x 28" Ext: 71" x 37" x 52"	-37°C to +177°C -35°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 35 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 3 Phase 60 Hz
LR-HD-521	21 Cubic Ft.	Int: 32" x 32" x 32" Ext: 76" x 41" x 52"	-37°C to +177°C -35°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 35 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 3 Phase 60 Hz
LR-HD-205	5 Cubic Ft.	Int: 20" x 22" x 20" Ext: 69" x 31" x 44"	-65°C to +177°C -85°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 60 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-208	8 Cubic Ft.	Int: 24" x 24" x 24" Ext: 70" x 33" x 48"	-65°C to +177°C -85°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 60 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-210	10 Cubic Ft.	Int: 28" x 24" x 27" Ext: 71" x 33" x 52"	-65°C to +177°C -85°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 60 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 1 Phase 60 Hz
LR-HD-213	13 Cubic Ft.	Int: 28" x 28" x 28" Ext: 71" x 37" x 52"	-65°C to +177°C -85°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 60 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 3 Phase 60 Hz
LR-HD-221	21 Cubic Ft.	Int: 32" x 32" x 32" Ext: 76" x 41" x 52"	-65°C to +177°C -85°F to +350°F	Room Ambient to Upper Limit in Approx. 20 Minutes	Room Ambient to Lower Limit in Approx. 60 Minutes	20% to 98% +/- 2% RH Limited by +2°C Dew Point	220V 3 Phase 60 Hz

Standard Features:

- Programmable Controller with RS232C
- Stainless Steel Interior
- Casters
- Multipane Viewing Window in Door
- Internal Light with External Switch
- 2" Diameter Access Port & Plug
- Adjustable High Temperature Safety (Digital Set Digital Indicating)

Options:

- IEEE-488 Computer Interface
- Chart Recorder
- Additional Ports
- Shelves
- CO₂ or LN₂ Option for Faster Pulldown
- Optional Voltage

Ultimate performance will be slightly affected by additional windows, ports and ambient air temperature.

In line with our corporate policy of continuing product improvement and quality control,

reserves the right to change product specifications without notice.