



Floor Type Vacuum Drying Oven

Large capacity Vacuum Drying Oven

For Information and to Order

Contact Us At:

323-7670-0634 800-574-2748

Email: sales@LRE.com

Web Site: www.LRE.com



Yamato Vacuum Oven Models: DP83C/103C

Operating temp. range 40~200°C

Operating pressure range 101~0.1kPa

Internal capacity 18 CuFt. DP83C
35 CuFt. DP103C

Large Scale Vacuum Drying Oven Designed for Treatment of Large-Sized Parts



■ Operation and function

- Vacuum pump can be installed inside the oven
- Quick connect / disconnect of vacuum pipes for easy vacuum pump maintenance
- Working efficiency is improved as exhaust system is improved to significantly shorten the time to reach vacuum
- Use specialized function menu key and up/down key to set. With program operation function, use submenu key to operate overheat protector, deviation correction, etc.

■ Safety features

- Self-diagnosis circuit (abnormal temperature sensing, heater disconnection, auto overheat prevention, SSR short circuit), overheat protector, ELB to prevent overcurrent, key lock, etc.
- For safety, resin protection panel is installed at the observation window


[Inquire For Discounted Prices](#)

Vacuum Oven Specs:

Model	DP83C	DP103C
Method	Decompressed chamber direct heating	
Operating temp. range	40~200°C	
Operating vacuum range	101~0.1kPa (760~1Torr)	
Temp. adjustment accuracy	±1.0°C (at 200°C)	
Interior material	Stainless steel plate	
Exterior material	Cold rolled steel plate with chemical proofing coating	
Insulating material	Glass fiber	
Heater power	6.5kW	14.4kW
Observation window	Toughened glass + resin protection panel	
Vacuum gauge	Pointer type, -100~0kPa	
Vacuum pump installation room	Yes	
Temp. control	3 segments PID	
Temp. setting	Use specialized function menu key and ▲/▼ key to set	
Temp. display	Measured temp. display: green 4-digit LED digital display Setting temp. display: red 4-digit LED digital display	
Timer	1min-99 hr 59 min and 100 hr-999 hr 50 min (with time wait function)	
Operation function	Fixed temp. auto start, auto stop, program operation	
Program mode	Program operation 3 segments 30 steps (30 steps×1, 15 steps×2, 10 steps×3)	
Additional function	Deviation correction, key lock, power outage compensation	
Heater circuit control	SSR driving	
Sensor	K thermocouple (temp. controller and overheat protector)	
Safety device	Self-diagnostic circuit (abnormal temp. sensing, heater disconnection, auto overheat prevention, SSR short circuit), overheat protector, EBL to prevent overcurrent, key lock, etc.	
Internal dimensions (W×D×H)	31.5" x 31.5" x 31.5"	39.3" x 39.3" x 39.3"
External dimensions (W×D×H)	40.1" x 40.1" x 72.8"	51.1" x 50.4" x 83"
Internal capacity	18 Cubic Ft.	35 Cubic Ft.
Air exhaust port	NW40 flange	
Air suction port	Rc 3/8	
Power source (50/60Hz) rated current	AC220V 31.5A no plug, round terminal	3 phase AC380V 27A no plug, round terminal
Weight	992 Lbs.	2204 Lbs
Included accessories	Stainless steel punching plates, 2 pcs.	Stainless steel punching plates, 4 pcs.
Optional accessories	Shelf plate, vacuum pump, N ₂ introduction device, recorder, alarm indicator lamp (stand-by/running/malfunction), external communication (RS485), temp. output terminal (4~20mA), Output terminal for external alarm, time up output terminal	

■ Options We Can Provide

Additional Shelves - Racks



Yamato Vacuum Oven Model DP83C/DP103C

Visit Our Web Site To View Our Inventory of NEW Yamato Ovens www.LRE.com

Or Call 323-770-0634 800-574-2748