

For Quality Refurbished -Warranted
Test Equipment Contact us at
800-574-2748 323-770-0634
Web Site: www.LRE.com



Note: Data Sheet For Reference Only - Actual Chamber May Vary Depending on Model Year, Options, Controllers, and Individual Configuration

Model 9076

Specifications

Test Volume	5.78 cubic feet (163.7 liters)
Internal Dimensions	20"H x 20"W x 25"D (50.80 x 97.16 x 95.3 cm)
Overall Dimensions	36 ¼"H x 38 ¼"W x 37 ½"D (92.08 x 97.16 x 95.3 cm)
Temperature Range	-73° to +315°C or -100°F to +600°F OPTION -184°C (-300°F) with optional LN ₂
Heat-up Rate	8°C / Minute
Cool-down Rate	12°C / Minute
LC02 Consumption	15 lbs/hr at -53°C (-65°F)
Air Circulation	Horizontal air flow pattern
Power Requirements	208 VAC, 50 or 60 Hz., three wire, single phase, 4800w 208 VAC, 50 or 60 Hz., four wire, single phase, 4800w 240 VAC, 50 or 60 Hz., single phase, 4800w
Net Wt. (Approx.)	232 lbs (105.9 Kg)

Used Refurbished - Warranted Test Chambers Available at LR Environmental 800-574-2748 323-770-0634
Visit Our Web Site To View Inventory www.LRE.com