

For Quality Refurbished -Warranted
 Test Equipment Contact us at
 323-770-0634 800-574-2748
 Web Site: www.LRE.com

**ENVIRONMENTAL
 EQUIPMENT & TEST LAB**



Note: Data Sheet For Reference Only - Actual Chamber May Vary Depending on Model Year, Options, Controllers, and Individual Configuration

Model 9064

LN2 Chamber Specifications

Test Volume 2.2 cubic feet (62.3 liters)

Internal Dimensions 12"H x 20"W x 16"D
 (30.48 x 50.80 x 40.64 cm)

Overall Dimensions 21 ½"H x 32 7/8"W x 30"D
 (54.61 x 83.66 x 76.20 cm)

Temperature Range -73° to +315°C or -100°F to +600°F
 OPTION -184°C (-300°F) with optional LN2

Heat-up Rate: 8°C / Minute

Cool Down Rate: 20°C / Minute

CO2 Consumption: 11.6 lbs/hr at -53°C (-65°F)

Air Circulation: Vertical air flow pattern

Power Requirements: 120 VAC, 50 or 60 Hz., single phase, 1800w 208
 VAC, 50 or 60 Hz., three wire, single phase,
 1800w 208 VAC, 50 or 60 Hz., four wire, single
 phase, 1800w 240 VAC, 50 or 60 Hz., single
 phase, 1800w

Net Wt. (Approx): 115 lbs (52.2 Kg)